

COLOR CHART FIBERGLASS

*Please select from the following Colors. Clear color is also available.
(Applied color appearance may vary because of surface texture, lighting, size, adjacent colors etc.)*



#122 So-TUF

WATER-BASED MAGNESITE SEALER

So-Tuf Sealer is a water-based coating designed for magnesite floors, decks and stairs. It is used as a sealer over new magnesite installations and as a re-coat for maintenance. It is also an excellent seal coat and water-resistant coating for all above grade masonry surfaces.

Thinning: For first coat on new magnesite, thin with water not to exceed 1½ gallons per 5 gallons. For second coat or recoating older work, use as packaged from factory.

Application: Use brush or roller, working back and forth until all voids are filled. (Be careful not to dry roll).

#212 ACRi-DEK

WATER-BASED COLORCOAT

Acri-Dek colorcoat is part of our Acri-Dek system. It is also used for the finish coat on elastomeric, cementitious decking, also concrete and asphalt for tennis courts, walkways, patios, balconies and most general decking.

Thinning: For porous and heavy textured finishes it may be necessary to thin. (Use water). Do not exceed 1½ gallons per 5 gallons. For smoother finishes and other surfaces, use as it comes from the factory.

Application: Use brush, roller or spray, making sure to get good penetration of all cracks, crevices and voids.



Natural



Antique White



Shadow Cream



Light Gray



Steel Gray



Tile Red

J
E
T
C
O
A
T
I
N
G
S
I
N
C.



Desert Sand



Dark Beige



Adobe



Putty



Wedgewood Blue



Dark Green

Color chips are subject to the effects of heat, light, age, and other processes and may vary slightly from the actual coating color.

Magnesite Diato Services



PH: (866) 864-0958

FAX: (866) 771-1114

sales@magnesitegroup.com

www.magnesitegroup.com

70680 Salton View Dr Mecca Ca 92254

Magnesite Diato Service *Satisfying Clients Since 1974!*